

PROFESSIONAL FOLDED DRAWINGS

Fast and effortlessly



Folder Express 3011

- Cut manual labour with efficient automation - there is no need to collect, trim, or fold prints by hand.
- Produce high quality folded documents efficiently and with great precision using proven Es-Te folding technology.
- Create a fully supported end-to-end workflow thanks to smooth integration with Canon printers and the ClearConnect Software suite.
- Realise sets of mixed size folded documents, up to A0 size.
- Print and fold documents up to 914 mm (36 inch) wide - ideal for CAD and GIS production.
- Maximise your productivity by stacking up to 80 folded A0 size documents on the automated delivery belt.
- Standardize your folding workflow with the help of 255 fold package templates or develop your own bespoke fold programs with WebTools Express.
- Reduce your footprint with the compact design of the Folder Express 3011. Combined with its low noise level it is the ideal solution for office environments.

TECHNICAL SPECIFICATIONS


Linear Folding speed	1 - 12 m/min, 39-472 in/min
Standard Fold programs	255 editable programs, of which 45 standard (DIN A, DIN B, DIN C, Fan Fold Only, Ericson, JPN, ANSI, ARCH, Mailer)
Document feed	Automatic
Document length fanfold only	420 mm - 6000 mm / 16.5 - 236 in up to 28 layers (80g/m ²)
Document length fanfold & crossfold	420 mm - 2500 mm / 16.5 - 98 in up to 17 layers (80g/m ²)
Document width	279 - 914 mm / 11 - 36 in
Paper weight	60 - 110 g/m ² ; 16 - 30 lb
Paper weight (recommended)	75 - 90 g/m ² ; 20 - 24 lb
Paper type (recommended)	Plain paper, bond paper
Package width	170 - 230 mm / 6.7 - 9.1 in (adjustable in 1 mm increments)
Package height	250 - 320 mm / 9.9-12.6 in (adjustable in 1 mm increments)

Folder Express 3011

Binding edge	0 - 40 mm; 0 - 1.5 in
Delivery capacity	80 A0/E size folded packages (80 g/m ²)
Power supply	110 - 120 V - 50/60 Hz 200 - 240 V - 50/60 Hz
Power consumption	Standby: <5W Max: 250W
Dimensions (LxWxH)	1780 x 860 x 1037-1253
Shipping dimensions (LxWxH)	1850 x 1070 x 1315 mm; 72.8 x 42.1 x 51.8 in
Weight	247 kg; 544 lb
Shipping weight	300 kg; 661 lb
Operating temperature	15 -35 °C; 59 - 95 °F
Operating humidity	20 - 80 % RH, depending on media type
Altitude	No limitation
User interface	7 inch, multi touch colour
Acoustic sound pressure	61 dB(A)



MDS Inovativne Tehnologije d. d.
Leskoškova cesta 9e, 1000 Ljubljana

 +386 1 586 79 33

 www.mds-it.si

 info@mds-it.si

