

imagePRESS C170 series

MAKING IT EASY FOR YOU TO DO MORE

A colour printer with office functionality and professional quality to broaden your print capabilities



- Transform blank sheets into a wide range of creative applications with professional in-line finishing capabilities and the ability to handle SRA3 and A4 paper sizes, media up to 350gsm and unique long-sheet functionality up to 1300mm
- Ensure brand colour consistency and expert colour control with the option to easily control colour management at a professional level
- Offer high quality output with accurate, precise and sharp image quality thanks to the imagePRESS R-VCSEL and 2400 x 2400 dpi print resolution
- A solution for any environment with easy installation, quick set-up and small footprint
- Multi-functional Embedded Application Platform (MEAP) ready platform and print anywhere functionality with uniFLOW Online and Mopria
- Connected multi-functional printer offering seamless integration with the cloud and secure, automated printing on-demand thanks to uniFLOW device management software
- Fast turnaround times up to 70 ppm in colour and 80 ppm in Bw* per minute both colour and monochrome printing and Up to 240 (mono) and 220 (colour) A4 images per minute scanning
- Increased confidentiality with system verification, real-time security information and user authentication login

*Print speeds referred to imagePRESS C170

Canon

TECHNICAL SPECIFICATIONS

imagePRESS C170 series

MAIN UNIT	A3 Colour Laser Multifunctional		Supported media sizes	Platen max. scanning size: 297.0 x 431.8 mm Document Feeder media size: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6R, Custom size (128.0 x 139.7 mm to 304.8 x 431.8 mm*) (*Long Sheet: up to 660 mm)
Machine type	Print, Copy, Scan, Send, Store and Optional Fax		Scan speed (ipm: BW/CL; A4)	Single-sided Scanning: 120/120 (300dpi), 120/70 (600 dpi) Double-sided Scanning: 240/220 (300dpi), 150/90 (600 dpi)
Core functions	Canon Dual Custom Processor (Shared)		Scan resolution (dpi)	600 x 600, 600 x 300, 300 x 600, 300 x 300
Processor	Standard: 25.6 cm (10.1 inch) TFT LCD WSVGA Colour Touch panel Optional UPRIGHT CONTROL PANEL-HI: 26.4 cm (10.4 inch) TFT LCD SVGA Colour Upright Touch Panel		Pull Scan specifications	Colour Network ScanGear2 for both TWAIN and WIA Supported OS: Windows* 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016
Control panel	Main CPU: 2 GB, Image Processing: 2 GB Standard: 250 GB, Maximum: 1 TB Optional: 250 GB, 1 TB		Scan method	Send functionality available on all models Scan to USB Memory Key: Available on all models Scan to Mobile Devices and cloud-based services: A range of solutions is available to provide scanning to mobile devices or cloud-based services depending on your requirements. Please contact your sales representatives for further information. TWAIN/WIA Pull scanning available on all models
Memory	Standard: 3,550 sheets 2 x 1100 sheet paper deck, 2 x 550 paper cassette and 250 sheet multi purpose tray Maximum: 7,050 sheets (with POD DECK LITE-C1 or PAPER DECK UNIT-E1)		SEND SPECIFICATIONS	
Hard Disk Drive	250 sheets (with Copy Tray-R2) Maximum: 5,000 sheets (with STAPLE FINISHER-W1 PRO or BOOKLET FINISHER-W1 PRO)		Destination	E-mail/Internet FAX (SMTP), SMB v3.0, FTP, WebDAV, Mail Box, Super G3 FAX (Optional), IP Fax (Optional)
Mirroring Hard Disk Drive	Paper Decks (1/2): 52-220 gsm Paper Cassettes (3/4): 52-256 gsm Multi-purpose tray: 52-350 gsm Optional PAPER DECK UNIT-E1: 52-256 gsm Optional POD DECK LITE-C1: 52-350 gsm Duplex: 52-220 gsm		Address book	LDAP (2,000), Local (1,600), Speed dial (200)
Paper supply capacity (A4, 80gsm)	Paper Decks (1/2): 52-220 gsm Paper Cassettes (3/4): 52-256 gsm Multi-purpose tray: 52-350 gsm Optional PAPER DECK UNIT-E1: 52-256 gsm Optional POD DECK LITE-C1: 52-350 gsm Duplex: 52-220 gsm		Send resolution (dpi)	600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200, 200 x 100, 150 x 150, 100 x 100
Paper output capacity (A4, 80gsm)	Quick Start Mode - On 4 sec or less (Time until key operations can be performed on the touch panel display) 30 sec or less (Time until it becomes possible to start copying) Quick Start Mode - Off 30 sec or less (Time until it becomes possible to start copying) From Sleep Mode: 30 seconds or less 689 (933*) x 941 x 1,220 mm		Communication protocol	File: FTP (TCP/IP), SMB v3.0, WebDAV E-mail/I-Fax: SMTP, POP3
Supported media weights	Approx. 264 kg (including Reader/DADF, Flat control panel and optional COPY TRAY-R2, excluding toner)		File format	Standard: TIFF, JPEG, PDF (Limited Colour, Compact, Searchable, Apply policy, Optimize for Web, PDF A/1-b, Encrypted), XPS (Compact, Searchable), Office Open XML (PowerPoint, Word), PDF/XPS (Device Signature) Optional: PDF (Trace & Smooth), PDF/XPS (User Signature)
Warm-up time	*With optional COPY TRAY-R2 *No tray extended		FAX SPECIFICATIONS	
Dimensions (W x D x H)	Approx. 264 kg (including Reader/DADF, Flat control panel and optional COPY TRAY-R2, excluding toner)		Maximum number of connection lines	1
Weight	*With optional COPY TRAY-R2 *No tray extended		Modem speed	Super G3: 33.6 kbps G3: 14.4 kbps
PRINT SPECIFICATIONS	C170	C165	Compression method	MH, MR, MMR, JBIG
Print speed (CL/BW)	70 ppm CL and 80 ppm BW (A4, A5, A5R, A6R)	65 ppm CL/BW (A4, A5, A5R, A6R)	Resolution (dpi)	400 x 400, 200 x 400, 200 x 200, 200 x 100
Print speed (CL/BW)	35 ppm CL and 40 ppm BW (A3), 33 ppm CL and 38 ppm BW (SRA3)	32 ppm CL/BW (A3), 31 ppm CL/BW (SRA3)	FAX memory	Up to 30,000 pages
Target (Max) print/copy volume per month	Up to 100,000 pages		STORE SPECIFICATIONS	
Monthly duty cycle	330,000 pages		Mail Box (Number supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes 30,000 Maximum Pages Stored
Front-back registration	Cross track: 2.0 mm or less, In track: 1.2mm or less		Advanced Space	Communication Protocol: SMB or WebDAV Supported Client PC: Windows* (Windows* 7 / 8 / 8.1 / 10) Concurrent Connections (Max.): <SMB> 64, <WebDAV> 3 (Active Sessions) Approx. 16 GB (Standard HDD)
Printing method	Colour Laser Beam Printing (Electronic Photography) 2,400 x 2,400		Advanced Space available disc space	Approx. 480 GB (with optional 1 TB HDD)
Print resolution (dpi)	Standard: UFR II, PCL 6, PCL5, Optional: PS		Advanced Space features	Authentication for Advanced Space Log-in, Sort Function, Printing a PDF File with a Password, imageWARE Secure Audit Manager Support Standard: USB Memory
Page description languages	Direct printing available from USB memory, Advanced Space, Remote UI and Web Access* Supported file types: TIFF, JPEG, PDF, EPS and XPS		Memory media	
Direct print	*Only PDF print from websites is supported Mopria, Canon Business Print and uniFLOW Online		SECURITY SPECIFICATIONS	
Printing from mobile and cloud	PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andale Mono WT J/K/S/T* (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts**		Authentication	Standard: Universal Login Manager (Device and Function Level Log-in), uniFLOW Online Express*, User Authentication, Department ID Authentication, Access Management System Optional: My Print Anywhere secure print (Requires uniFLOW)
Fonts	*Requires optional PCL INTERNATIONAL FONT SET-A1 **Require optional BARCODE PRINTING KIT-D1		Data	* No charge for this solution; however activation is required. Please contact your sales representatives for further information. Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Common Criteria Certification (DIN ISO 15408) Optional: Hard Disk Drive Mirroring, Data Loss Prevention (Requires uniFLOW)
Operating System	PS fonts: 136 styles UFR II: Windows* 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016 / Server 2019, Mac OS X (10.9 or later) PCL: Windows* 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016 / Server 2019 PS (Driver): Windows* 7 / 8.1 / 10 / Server 2008 / Server 2008 R2 / Server 2012 / Server 2012 R2 / Server 2016 / Server 2019, Mac OS X (10.9 or later) PS (PPD): Windows* 7 / 8.1 / 10, Mac OS X (10.3.9 or later)		Network	Standard: IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME Standard: Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device Signature, Secure Watermarks, User Signature, Document Scan Lock
COPY SPECIFICATIONS	C170	C165	Document	
Copy speed (CL/BW)	70 ppm CL and 80 ppm BW (A4, A5, A5R, A6R), 35 ppm CL and 40 ppm BW (A3), 33 ppm CL and 38 ppm BW (SRA3)	65 ppm CL/BW (A4, A5, A5R, A6R), 32 ppm CL/BW (A3), 31 ppm CL/BW (SRA3)	ENVIRONMENTAL SPECIFICATIONS	
First-Copy-Out Time (A4) (BW/CL)	Approx. 4.8/5.9 seconds (20-30 °C Environment)		Operating environment	Temperature: 20-27 °C Humidity: 15-60 % RH (Relative Humidity without condensation) C165: 220-240 V (±10 %), 50/60 Hz (±2 Hz), 10 Amp C170: 220-240 V (±10 %), 50/60 Hz (±2 Hz), 11 Amp CEE 7/7 (230V)
Copy resolution (dpi)	Scan: 600 x 600 Print: Up to 2,400 x 2,400 Up to 9,999 copies		Power source	C165 Approx. 2,000 W; C170 Approx. 2,500 W Printing: Approx. 1,472 W ^{*1} Standby: Approx. 136.6 W ^{*1} Sleep mode: Approx. 0.9 W ^{*2} Plugin Off: Approx. 0.2 W ^{*3}
Multiple Copies	Automatic or Manual (9 Levels) Up to 9,999 copies		Plug (Main Unit)	
Copy density	Automatic or Manual (9 Levels)		Power consumption	
Magnification	25% - 400% (1% Increments)		Standards	Blue Angel
Preset reductions	25%, 50%, 70%			
Preset enlargements	141%, 200%, 400%			
SCAN SPECIFICATIONS	Colour Platen and Single-pass Duplexing Automatic Document Feeder* [2-sided to 2-sided (Automatic)]			
Type	*Detect Feeder Multi Sheet Feed is supported. 300 Sheets			
Document Feeder paper capacity (80 gsm)	Sheet, Book, 3-Dimensional objects Document Feeder media weight: 1-sided scanning: 38-220 gsm (BW), 64-220 gsm (CL) 2-sided scanning: 50-220 gsm (BW), 64-220 gsm (CL)			
Acceptable originals and weights				

TECHNICAL SPECIFICATIONS

imagePRESS C170 series

CONSUMABLES

Toner cartridges

T-07 TONER BK/C/M/Y

SOFTWARE AND PRINTER MANAGEMENT

Tracking and reporting

Universal Login Manager (ULM):
Manage your costs easily by using the embedded reporting capability to identify and control costs on a user-based level by device.

uniFLOW Online Express:

Combining with ULM you can gain further control, highlight expenditures per users/department and pinpoint where costs can be scaled down from a central cloud based location.

Remote management tools

iW Management Console:

Server-based software for centralised management of a fleet of devices (includes monitoring or consumables, status monitoring and alerts, distribution of address books, configuration settings, firmware and MEAP applications, meter capture and reporting, driver and resource management)

eMaintenance:

Compatible with eMaintenance services via embedded RDS (Enables meter capture, automatic consumables management, remote diagnostics and reporting for service providers to offer efficient, fast and proactive maintenance)

Content Delivery System:

Allows the Remote distribution of firmware, iR options and MEAP applications; Remote User Interface (RUI) Web based interface to each device that helps to provide remote device management and control

Scanning software

Network ScanGear:

TWAIN-compliant scanner driver that enables computers on a network to use the pull scan functionality of the device

Optimisation tools

Canon Driver Configuration Tool:

A utility for changing the factory default settings of Canon print drivers

Platform

MEAP (Multifunctional Embedded Application Platform):

A powerful JAVA Embedded Platform for Canon devices which provides tight coupling between a range of software solutions and the device.

MEAP Web:

Web service alternative to MEAP that allows MFP applications to be developed and deployed via web services

Document publishing

iW Desktop:

Powerful print publishing software which easily combines documents from different sources and file formats, applies finishing with preview and templates to create professional looking documents. Includes PDF creation, annotation and compression capabilities for simple digital workflows such as proofing and authorisation.

FIERY PRINT CONTROLLER SPECIFICATIONS

Optional/Standard

Optional

Name

<Embedded type> imagePRESS Server M10

Print resolution (dpi)

<Server type> imagePRESS Server L30

Page Description Language(s)

1200 x 1200, 600 x 600

Memory

Adobe PS3, PCL6

Hard Disk Drive

<Embedded> 4 GB (1 x 4 GB)

Processor speed

<Server> 8 GB (2 x 4 GB)

System

500 GB SATA

Fonts

<Embedded> Intel Pentium G4400 (3.3 GHz)

Supported Operating Systems

<Server> Intel Core i3-6100 (3.7 GHz)

Network protocols

<Server> Fiery FS400 Pro

Direct print

PCL: 113 Fonts

VDP

Windows® 7 (64 bit) / 8.1 (64 bit) / 10 (64 bit) / Server 2012 (64 bit only) / Server 2012 R2 (64 bit only) / Server 2016 R2 (64 bit only) / Server 2019 (64 bit only)

Fiery print controller standard features

MAC OS (10.11, 10.12, 10.13, 10.14)

Fiery print controller options

TCP/IP (FTP, SMTP, POP, HTTP, SNMP, LDAP, SLP, SMB, LPD, IPP, WS-Discovery, Bonjour, Direct Mobile Printing, Port9100, SNMP, 802.1X, DHCP, DNS, NTP)

Hardware platform

PDF1.7, EPS, TIFF6, JDF1.4/JMF(OP)

Base OS

<Embedded> FreeForm v1/v2.1

Power source

<Server> FreeForm v1/v2.1, PPML, PDF/VT-1, PDF/VT-2, Creo VPS

Maximum Power consumption

<Embedded> E400

Dimensions (W x D x H)

<Server> NX One

Weight

Debian of Linux <Embedded> Windows® 10 IoT Enterprise 2016 LTSB <Server> AC100-240V, 50HZ/60HZ, 3.0A (100V) - 1.5A (240V)

PAPER SUPPLY OPTIONS

Paper Deck Unit-E1

Paper Capacity: 3,500 sheets (80 gsm)
Paper Type: Thin, Plain, Recycled, Thick, Colour, Pre-punched, Letterhead, Bond
Paper Size: A4, B5, LTR*
Paper Weight: 52-256 gsm
Power Source: From the main unit
Dimensions (W x D x H): 340 x 630 x 572 mm (attached to the main unit) Weight: Approx. 34 kg

POD Deck Lite-C1

*Media size change requires service technicians
Paper Capacity: 3,500 sheets (80 gsm)
Paper Type: Thin, Plain, Recycled, Thick, Colour, Pre-punched, Letterhead, Bond, Tab, Transparency, Label, Coated, Textured, Tracing, Envelope*
Paper Size: A3, B4, A4, A4R, B5, B5R, A5R, SRA3, 11"x17", LGL_R, LTR, LTR_R, EXE, STMT_R, 12"x18", 13"x19", BK, 16K, 16K_R, Envelope [No.10(COM10), Monarch, DL, ISO-C5], Custom size (139.7 x 148.0 mm to 330.2 x 487.7 mm)
Paper Weight: 52-350 gsm
Power Source: 220-240V, 50/60Hz, 1.2A
Dimensions (W x D x H): 633 x 686 x 574 mm (attached to the main unit) Weight: Approx. 68 kg

OUTPUT OPTIONS

Copy Tray-R2

Provides a simple tray for basic output needs.
Capacity: 250/100 sheets (1-sided/2-sided, 80 gsm)

Staple Finisher-AC1 (External)

Lower Tray (A) Capacity:
A4/A5R/B5 3,000 sheets (80 gsm), SRA3/A3/A4R/B4/B5R/13"x19" 1,500 sheets (80 gsm), A6R 250 sheets*1 (80-105 gsm), Envelope 30/100 sheets (Monarch/Others), Long sheet*2 (Over 487.7 mm up to 762 mm length) 100 sheets (79 gsm),
Long sheet*3 (Over 762 mm length) 1 sheet (holding by hand),
All size of thin paper (52-63 gsm) 1,500 sheets,
Capacity for coated paper is half of that for plain paper
*1 A6R 50 sheets (106 gsm and above)
*2 Optional LONG SHEET TRAY-B1 is required
Upper Tray (B) Capacity:
A4/A5R/B5 250 sheets (80 gsm), SRA3/A3/A4R/B4/B5R/13"x19" 125 sheets (80 gsm)
Mid Tray (C) Capacity:
A4/A5R/B5 250 sheets (80 gsm), SRA3/A3/A4R/B4/B5R/13"x19" 125 sheets (80 gsm)
Paper Weight for Tray A:
<Non Sort> 52-350 gsm, <Bunch Shift and Staple> 52-256 gsm, <Eco Staple> 52-105 gsm
*Excluding duplex printed thin paper (52-63 gsm) and any special media (Tracing, Transparency, Label)
Paper Weight for Tray B/C:
<Non Sort and Bunch Shift> 52-256 gsm*
*Excluding duplex printed thin paper (52-63 gsm)
Staple Position: Corner, Double
Staple Capacity: <Non coated media, 52-90 gsm> A4 65 sheets, A3/A4R 40 sheets, <Coated media> 2 sheets
Power Source: From the main unit
Dimensions (W x D x H): 527 (Max 656*) x 623 x 1,099 (Max 1,195*) mm
*when the auxiliary tray is extended.
Weight: Approx. 36 kg

Booklet Finisher-AC1 (External)

Tray Capacity / Paper Weight / Staple Position / Staple Capacity: same as STAPLE FINISHER-AC1 but if there are any sheets on the saddle tray, the capacity of Tray A becomes limited to 1,500 sheets
Booklet Stitch Paper Size: A3, A4R, B4, Custom size (195 x 270 mm to 304.8 x 457.2 mm)
Booklet Stitch Paper Weight: Body sheet 52-220 gsm, Cover sheet 52-256 gsm
Booklet Stitch Staple Capacity (including 1 cover sheet):
<Non coated media> 20 sheets (52-81.4 gsm), 10 sheets (82-105 gsm), 5 sheets (106-150 gsm), 4 sheets (151-209 gsm), 3 sheets (210-220 gsm), <Coated media> 5 sheets (85-150 gsm), 4 sheets (151-209 gsm), 3 sheets (210-220 gsm)
Non Staple Folded Bunch Capacity: <Non coated media> 3 sheets (52-105 gsm), 1 sheet (106-256 gsm), <Coated media> 1 sheet
Power Source: From the main unit
Dimensions (W x D x H): 527 (Max 656*) x 623 x 1,099 (Max 1,195*) mm
*when the auxiliary tray is extended.
Weight: Approx. 60 kg

Finisher Jogger Kit-A1

Attached to the Lower Tray (A) of either the STAPLE FINISHER-AC1 or BOOKLET FINISHER-AC1
Paper Size: <Non Sort> A3, A4, A4R, B4, B5, B5R, <Bunch Shift> A3, A4, A4R, B4, B5
Paper Weight: <Non Sort> 52-300 gsm, <Bunch Shift> 52-256 gsm

Staple Finisher-W1 PRO (External)

Upper Tray (A) Capacity:
SRA3/A3/A4/A4R/A5/A5R/A6R/B4/B5/B5R/13"x19" / Custom size (100 x 148.0 mm to 330.2 x 487.7 mm), 1,000 sheets*1 (80 gsm),
Envelope [No.10(COM10), Monarch, DL, ISO-C5, Custom size (100 x 148.0 mm to 330.2 x 487.7 mm)] 150 sheets, Z-fold 30 sheets (A3/B4), Half-fold 50 sheets (A4R),
Long sheet*2 (210 x 487.8 mm to 330.2 x 762 mm) 100 sheets (52-79 gsm) / 50 sheets (80-150 gsm) / 25 sheets (151-300 gsm) / 20 sheets (301-350 gsm),
Long sheet*3 (Over 762 mm up to 1,300 mm length) holding by hand,
*1 301-350 gsm: 200 sheets regardless of size
*2 Optional LONG SHEET TRAY-B1 is required
Lower Tray (B) Capacity:
A4/B5 4,000 sheets*3 (80 gsm), A4R/B5R 2,000 sheets*4 (80 gsm), A3/B4 1,500 sheets*4*5 (80 gsm), SRA3/13"x19" 1,000 sheets (80 gsm), Any size 200 sheets (301-350 gsm), Z-fold 30 sheets (A3/B4)
*4 A4/B5 2,000 sheets (52-63 gsm)
*5 A3/A4R/B4/B5R 1,000 sheets (52-63 gsm)
*6 A3/B4 coated paper: 1,000 sheets
Paper Weight: 52-350 gsm
Staple Position: Corner, Double
Staple Capacity: <Non coated media> A4/B5 100 sheets, A3/A4R/B4/B5R 50 sheets, <Coated media> A4/B5 40 sheets, A3/A4R/B4/B5R 30 sheets
Power Source: 220-240V, 50-60Hz, 8A
Dimensions (W x D x H): 800 x 792 x 1,239 mm (with LONG SHEET TRAY-B1: 1,136 x 792 x 1,239 mm)
Weight: Approx. 130 kg



TECHNICAL SPECIFICATIONS

imagePRESS C170 series

<p>Booklet Finisher-W1 PRO (External)</p>	<p>Tray Capacity / Paper Weight / Staple Position / Staple Capacity: same as STAPLE FINISHER-W1 PRO but if there are any sheets on the saddle tray or the optional BOOKLET TRIMMER-F1 is attached, the capacity of Tray B becomes limited Booklet Stitch Paper Size: A3, A4R, B4, SRA3, 13"x19", Custom size (210 x 279.4 mm to 330.2 x 487.7 mm) Booklet Stitch Paper Weight: Textured, Bond, Coated, Tab, Cover sheet 64-300 gsm Booklet Stitch Staple Capacity (including 1 cover sheet): <Non coated media> 25 sheets (52-80 gsm), 15 sheets (80.1-105 gsm), 5 sheets (105.1-209 gsm), 4 sheets (209.1-220 gsm), <Coated media> 10 sheets (100-128 gsm), 5 sheets (128.1-209 gsm), 4 sheets (209.1-220 gsm) Non Staple Folded Bunch Capacity: up to 5 sheets (52-209 gsm) Power Source: 220-240V, 50-60Hz, 8A Dimensions (W x D x H): 800 x 792 x 1,239 mm (with LONG SHEET TRAY-B1: 1.136 x 792 x 1,239 mm) Weight: Approx. 180 kg</p>	<p>Document Insertion Unit-N1</p>	<p>Requires either the STAPLE FINISHER-W1 PRO or BOOKLET FINISHER-W1 PRO Number of Trays: 2 Tray Capacity: Upper Tray 200 Sheets (80 gsm), Lower Tray 200 Sheets (80 gsm) Paper Type for Insertion: Thin, Plain, Recycled, Colour, Thick, Pre-punched, Letterhead, Bond, Coated, Tab, Tracing, Textured Paper Size for Insertion: SRA3, A3, A4, A4R, B4, B5, B5R, 13"x19", Custom size (182.0 x 182.0 mm to 330.2 x 487.7 mm) Paper Weight for Insertion: 52-300 gsm Power Source: 100-240V, 50/60Hz, 1.0A Dimensions (W x D x H): 336* x 793 x 1,407 mm (*width excluding document tray) Weight: Approx. 61 kg</p>
<p>2/4 Hole Puncher Unit-A1</p>	<p>Attached inside of either the STAPLE FINISHER-AC1 or BOOKLET FINISHER-AC1 2 or 4 Holes (FRN) Paper Weight: 52-300 gsm Paper Size: 2 holes A3, A4, A4R, B4, B5, B5R; 4 holes A3, A4 Power Source: From the finisher</p>	<p>Paper Folding Unit-J1</p>	<p>Requires either the STAPLE FINISHER-W1 PRO or BOOKLET FINISHER-W1 PRO Supported Folding Type: Z-Fold, Accordion Z-Fold, C-Fold, Half-Fold, Double Parallel Fold Paper Type: Thin, Plain, Recycled, Colour, Bond Paper Sizes: <Z-Fold> A3, A4R, B4 <Accordion Z-Fold, C-Fold, Half-Fold, Double Parallel Fold> A4R Paper Weight: <Z-Fold, Accordion Z-Fold, C-Fold, Half-Fold> 52-105 gsm <Double Parallel Fold> 52-90 gsm Power Source: From the finisher Dimensions (W x D x H): 336 x 793 x 1,190 mm Weight: Approx. 71 kg</p>
<p>4 Hole Puncher Unit-A1</p>	<p>Attached inside of either the STAPLE FINISHER-AC1 or BOOKLET FINISHER-AC1 4 Holes (SWE) Paper Weight: 52-300 gsm Paper Size: A3, A4, A4R, B4, B5, B5R Power Source: From the finisher</p>	<p>HARDWARE ACCESSORIES</p>	<p>Card Readers</p> <p>MiCARDPLUS FOR ULM - A proximity card reader for card based user authentication, supporting multiple card technologies (HID, HiTag, Casi Rusco, Indala and MiFare etc.). Integrates with Universal Login Manager and uniFLOW COPY CARD READER-F1 - Magnetic physical card access system. (Integrates with Department ID, not for use with uniFLOW) COPY CARD READER ATTACHMENT-A4 - Attachment kit for COPY CARD READER-F1.</p>
<p>Puncher Unit-BT1 (2/F4H)</p>	<p>Attached inside of either the STAPLE FINISHER-W1 PRO or BOOKLET FINISHER-W1 PRO 2 or 4 Holes (FRN) Paper Weight: 52-300 gsm Paper Size: 2 holes A3, A4, A4R, A5L, B4, B5, B5R, Custom size (182 x 182 mm to 297 x 432.0 mm excluding 203 x 257 mm to 297 x 270 mm); 4 holes A3, A4, B4, B5, Custom size (257 x 182 mm to 297 x 432 mm) Power Source: From the finisher</p>	<p>SECURITY OPTIONS</p>	<p>Document Security</p> <p>Function of DOCUMENT SCAN LOCK KIT is implemented as standard - Increases document security by embedding hidden track and lock code within copied or printed documents to restrict unauthorised copying, sending, and faxing Data Security</p> <p>HDD MIRRORING KIT-J1 - Enables replication of data in case of disk hardware failure so that data can be recovered. 2.5INCH/250GB HDD-N1 - Additional HDD required for the hard disk mirroring function. 2.5INCH/1TB HDD-P1 - A replacement HDD to increase the storage space on the device. Note: The mirroring function requires a second 1TB HDD.</p>
<p>Puncher Unit-BU1 (S4H)</p>	<p>Attached inside of either the STAPLE FINISHER-W1 PRO or BOOKLET FINISHER-W1 PRO 4 Holes (SWE) Paper Weight: 52-300 gsm Paper Size: A3, A4, A5L, B4, B5, Custom size (257 x 182 mm to 297 x 432 mm) Power Source: From the finisher</p>	<p>SYSTEM AND CONTROLLER OPTIONS</p>	<p>Print Accessories</p> <p>PCL INTERNATIONAL FONT SET-A1 - Adds PCL support for Andale Mono WT J/K/S/T (Japanese/Korean/Simplified Chinese)/Traditional Chinese.</p>
<p>Multi Function Professional Puncher-B1</p>	<p>Requires either the STAPLE FINISHER-W1 PRO or BOOKLET FINISHER-W1 PRO Paper Weight: <Through> 52-350 gsm (Plain paper), 106-350 gsm (Coated paper) <Punch> 75-300 gsm (Plain paper), 118-300 gsm (Coated paper) Paper Size: <Through> 100 x 148 mm to 330.2 x 1,300 mm <Punch> SRA3, A3, SRA4, SRA4R, A4, A4R Punch Tools: Plastic Comb 21-Hole, Twin Loop 23-Hole (Round/Square), Twin Loop 34-Hole (Round/Square), Color Coil 47-Hole, Velo Bind 12-Hole, Loose Leaf 4-Hole Punch, Loose Leaf 2-Hole Punch, Loose Leaf 4-Hole (Swedish), Crease Power Source: 230V, 50Hz, 2.0A Dimensions (W x D x H): 445 x 795 x 1,040 mm Weight: Approx. 102 kg</p>	<p>Send Options</p>	<p>Function of UNIVERSAL SEND DIGITAL USER SIGNATURE KIT is implemented as standard - Ensures the authenticity of a PDF/XPS by identifying the user that sent the document through a visible and/or invisible digital signature. Function of UNIVERSAL SEND TRACE & SMOOTH PDF KIT is implemented as standard - Enables the device to create and send Trace and Smooth PDF. BARCODE PRINTING KIT-D1 - Provides the ability to print 1D and 2D barcodes on output using jet caps technology.</p>
<p>Booklet Trimmer-F1</p>	<p>Requires BOOKLET FINISHER-W1 PRO Trim Width: 2-28 mm Trim Thickness: Up to 50 sheets (include cover) Paper Weight: 52-300 gsm Paper Size: SRA3, A3, A4R, B4, 13"x19", Custom size (210.0 x 279.4 mm to 330.2 x 487.7 mm) Chip Tray Capacity: Approx. 5,000 sheets (Trim width 20mm, A4, 80 gsm) Power Source: From the finisher Dimensions (W x D x H): 2,095 (including joint, conveyor and output tray) x 790 x 1,040 mm Weight: Approx. 178 kg (including conveyor and output tray)</p>	<p>Barcode Printing</p>	<p>SYSTEM ACCESSORIES</p> <p>COPY CONTROL INTERFACE KIT-A1 - Allows connection (CCV1 I/F) between 3rd party copy control terminal and Canon's iR-ADV range for cost recovery use. SERIAL INTERFACE KIT-K3 - Serial Interface for Cost Recovery Solutions. CONNECTION KIT-A1 for BLUETOOTH LE - Bluetooth chip is an option for enabling the communication between the main unit and other devices using Bluetooth NFC CONTROL PANEL-A1 - NFC Control Panel is an optional kit enabling the communication between the main unit and other devices using NFC. This is used with the optional UPRIGHT CONTROL PANEL-H1. NFC CONTROL PANEL-C1 - NFC Control Panel is an optional kit enabling the communication between the main unit and other devices using NFC. This is used with the standard flat control panel.</p>
<p>Document Insertion / Folding Unit-K1</p>	<p>Requires either the STAPLE FINISHER-AC1 or BOOKLET FINISHER-AC1 Number of Trays: 1 Tray Capacity: 100 Sheets (80 gsm) Supported Folding Type: Z-Fold, C-Fold Paper Type: <Z-Fold/C-Fold> Thin, Plain, Recycled, Colour, <Insertion Unit> Thin, Plain, Recycled, Colour, Thick, Letterhead, Bond, Coated, Tab, Textured Paper Size: <Z-Fold> A3, A4R, B4, <C-Fold> A4R, <Insertion Unit> SRA3, A3, A4, A4R, B4, B5, B5R, 13"x19" Paper Weight: <Z-Fold/C-Fold> 60-105 gsm, <Insertion Unit> 60-256 gsm Power Source: 100-240V, 50/60Hz, 1.0A Dimensions (W x D x H): 247* x 679 x 1,242 mm (*width excluding document tray) Weight: Approx. 76 kg</p>		



MDS Inovativne Tehnologije d.d.
Leskoškova cesta 9e, 1000 Ljubljana

386 1 586 79 33

www.mds-it.si

info@mds-it.si

