

imagePROGRAF PRO-6000

LARGE FORMAT PHOTOGRAPHIC AND ART PRINTING HAS NEVER BEEN SO IMPRESSIVE.

The 60-inch large format printer in a league of its own – with peerless print quality, productive output speeds and supreme reliability.



KEY FEATURE

- Class-leading print quality for a 60-inch model, with LUCIA PRO 12-colour ink system
- Productive print speeds realized by the 1.28-inch-wide print head
- Efficient workflow enabled by dual-roll unit, offering continuous feeding and automatic paper take-up
- Space-saving compact and attractive body
- Simplified user operation thanks to 3.5-inch colour touch screen
- Newly developed multi-position basket allows for numerous configuration options
- Fast and easy printing of PDF and JPEG file formats directly from USB memory stick
- Quick and easy Wi-Fi connectivity
- Minimised maintenance and production interruptions from high-capacity “hot swap” ink tanks
- Reliable performance and guaranteed colour consistency across every unit

PRODUCT RANGE



Canon imagePROGRAF PRO-6000



Canon imagePROGRAF PRO-4000



Canon imagePROGRAF PRO-2000



Canon imagePROGRAF PRO-1000

Canon

TECHNICAL SPECIFICATIONS

imagePROGRAF PRO-6000

TECHNOLOGY

Printer Type	12 Colour 60"/1524mm
Print Technology	Canon Bubblejet on Demand 12 colours integrated type (12 chips per print head x 1 print head)
Print Resolution	2,400 x 1200 dpi
Number of Nozzles	18,432 nozzles (1536 nozzles x 12 colour)
Line Accuracy	±0.1% or less
	User adjustments necessary. Printing environment and media must match those used for the adjustments. CAD paper required: Plain paper, CAD tracing paper, coated paper, CAD translucent matte film only
Nozzle Pitch	600 dpi x 2 includes Non-firing nozzle detection and compensation system
Ink Droplet Size	minimum 4 pl per colour
Ink Capacity	Sales Ink: 160ml/330ml/700ml Bundled Starter Ink: 330ml
Ink Type	Pigment inks - Black, Matte Black, Cyan, Magenta, Yellow, Photo Cyan, Photo Magenta, Grey, Photo Grey, Red, Blue, Chroma Optimiser
OS Compatibility	Microsoft Windows 32 Bit: Vista, 7, 8, 8.1, 10, Server 2008, 64 Bit: Vista, 7, 8, 8.1, 10, Server 2008/R2, Server 2012/R2 Apple Macintosh: OS X 10.7.5 - 10.11
Printer Languages	SG Raster (Swift Graphic Raster), PDF (Ver.1.7), JPEG (Ver. JFIF 1.02)
Standard Interfaces	USB A Port: USB Memory Direct Print for JPEG/PDF files USB B Port: Built-in Hi-Speed USB 2.0 Ethernet: 10/100/1000 base-T Wireless LAN: IEEE802.11n/IEEE802.11g/IEEE802.11b *Please refer to user manual how to activate/deactivate the wireless LAN

MEMORY

Standard memory	3 GB
Hard Drive	320 GB

PRINT TIME FOR A0 PAGE SIZE

	Print Mode	Print Time
Plain Paper	Fast	1:37 min
	Standard	2:51 min
Coated Paper	Print Mode	Print Time
	Standard	2:51 min
	High Quality	5:36 min
Glossy Photo Paper	Print Mode	Print Time
	Standard	6:21 min
	High Quality	10:05 min

MEDIA HANDLING

Media Feed and Output	Upper Roll Paper: One Roll, Front-loading, Front Output Lower Roll Paper: One Roll, Front-loading, Front Output Cut Sheet: Front-loading, Front Output (Manual feed using media locking lever)
Media Width	Roll paper: 203.2 -1524 mm Cut sheet: 203.2 - 1524 mm
Media Thickness	Roll/Cut: 0.07 - 0.8 mm
Minimum Printable Length	203.2 mm
Maximum Printable Length	Roll paper: 18 m (Varies according to the OS and application) Cut sheet: 1.6 m
Maximum Media Roll Diameter	170 mm
Media Core Size	Internal diameter of roll core: 2"/3"
Margins Recommended area	Roll paper: Top: 20 mm, Bottom: 3 mm, Side: 3 mm Cut sheet: Top: 20 mm, Bottom: 20 mm, Side: 3 mm

Margins Printable area

Roll paper: Top: 3 mm, Bottom: 3 mm, Side: 3 mm
Roll paper (borderless): Top: 0 mm, Bottom: 0 mm, Side: 0 mm
Cut sheet: Top: 3 mm, Bottom: 20 mm, Side: 3 mm

Media Feed Capacity

Roll Paper: Two rolls. Automatic switching is possible.
Cut Sheet: 1 sheet

Media Take-up roll unit

Dual direction roll take up unit allowing print surface to be wound inside or outside of the roll

Borderless Printing Width (Roll Only)

515 mm (JIS B2), 728 mm (JIS B1), 1030 mm (JIS B0), 594 mm (ISO A1), 841 mm (ISO A0), 10", 14", 17", 24", 36", 42", 44", 50", 54", 60", 257 mm (JIS B4)*, 297 mm (ISO A3)*, 329 mm (ISO A3+)*, 420 mm (ISO A2)*, 8", 16", 30", 300 mm*

*Some environmental conditions may not produce the desired result

Maximum number of delivered prints

Standard position: 1 sheet
Flat position: A2 landscape, glossy paper less than 10 sheets, Coated paper less than 20 sheets (excludes strong curled condition)

DIMENSIONS AND WEIGHT

Physical Dimensions WxDxH (mm) and Weight (Kg)

1999 x 984 x 1168 mm (Basket Open)
1999 x 766 x 1168 mm (Basket Closed)
167 kg (including Roll Holder Set and Roll unit, excluding ink and print heads)

Packaged Dimensions WxDxH (mm) and Weight (Kg)

Printer (Main unit with pallet): 2227 x 915 x 1022 mm
210 kg
Roll Unit: 2133 x 562 x 461 mm
40 kg

POWER AND OPERATING REQUIREMENTS

Power Supply

AC 100-240V (50-60Hz)

Power Consumption

Operation: 103 W or less
Sleep mode: 3.6W or less
Default setting for the time to enter the Sleep mode: Approx. 5 Minutes
Power off: 0.3 W or less

Operating Environment

Temperature: 15-30°C, Humidity: 10-80% RH (no dew condensation)

Acoustic Noise (Power/Pressure)

Operation: 50 dB (A) (Glossy paper, Print priority: Standard)
Standby: 35 dB (A) or less
Operation: 6.7 Bels or less (Glossy paper, Image, Print priority: Standard) (Measured on ISO 7779 standard)

Regulations

Europe: CE mark, Russia: EAC,
Other countries: CB certification

Environment Certificates

International Energy Star Program (WW), RoHS

WHAT'S INCLUDED

What's in the Box?

Printer, Roll Unit, 1 x Print Head, 1 x Maintenance Cartridge, 3" Paper Core Attachment, EU & UK Power Cable, 1 Set of Starter Ink Tanks, Set Up Guide, Safety/Standard Environment Leaflet, User Software CD-ROM (OSX/Windows), PosterArtist Lite CD-ROM, EU Biocide Sheet, Eurasian Economic Union Sheet, Important Information Sheet, Quick Guide and Printhead Alignment Sheet

Software Included

imagePROGRAF PRO Printer Driver, Print Plug-In for Office, Quick Utility Toolbox and PosterArtist Lite
Other software available as Download from Web.

OPTIONS

Optional Items

2/3" Roll Holder: RH2-45

CONSUMABLES



+386 1 586 79 33

www.mds-it.si

info@mds-it.si

MDS Inovativne Tehnologije d. d.
Leskoškova cesta 9e, 1000 Ljubljana

