Specifications							
Item		CE7000-40	CE7000-60	CE7000-130	CE7000-160 (Not available in US & Korea)		
		Grit rolling type			,		
		Digital servo drive					
		375mm × 50m	603mm × 50m	1270mm × 50m	1524mm × 50m		
Cutting area of guarante		355mm× 2m	583mm × 2m	1250mm × 2m	1504mm × 2m		
(When using optiona			(583mm × 5m)	(1250mm × 5m)	(1504mm × 5m)		
Mountable	Min.	50mm					
media width	Max.	484mm (19inch)	712mm (28inch)	1372mm (54inch)	1626mm (64inch)		
Mountable roll media	a mass	5kg	9kg	17kg	20kg		
Number of push rolle	ers	2 rollers 4 rollers (Max. 5 (option))					
Max. cutting speed		600mm/s at all direction	900mm/s at 45° direction	1000mm/s at 45° direction			
Acceleration		Max. 21.2m/s² at 45° direction Max. 13.9m/s² at 45° direction					
Cutting force		Max. 4.41N (450gf)					
Minimum character s	size	Approx. 5 mm alphanumeric (varies depending on character font and media)					
Mechanical resolution		0.005mm					
Programmable resolution		GP-GL: 0.1/0.05/0.025/0.01mm HP-GL™ (*2): 0.025mm					
Repeatability (*1)		Max. 0.1 mm in plot up to 2 m (Excluding media expansion and contraction)					
Mountable number of tools		1 tool					
Blade types		Supersteel					
Pen types		Oil-based ballpoint pen, Water-based fiber-tip pen					
Media types		Up to 0.25mm thickness					
		Marking film (PVC / fluorescence / reflection), polyester film (With specified conditions)					
Interface		USB 2.0(Full Speed), Ethernet 10BASE-T/100BASE-TX					
Buffer memory		2MB					
Command sets		GP-GL / HP-GL™ (Set by command or auto-detect) (*2)					
Display		Graphic type LCD with back-light (240dots x 128dots), supports 10 languages					
Power source		100V to 120V AC, 200V to 240V AC,	50 / 60 Hz				
Power consumption Up to 100W							
Operating environme	ent	10 to 35 °C, 35 to 75 % R.H. (non-condensing)					
		16 to 32 °C, 35 to 70 % R.H. (non-condensing)					
External dimensions	(W x D x H)	Approx. 772 x 292 x 313 mm	Approx. 1005 × 582 × 1092 mm	Approx. 1704 × 811 × 1215 mm	Approx. 1916 × 811 × 1215 mm		
(with basket)			(1005 × 936 × 1092 mm)(*3)	(1704 × 1148 × 1215 mm)(*3)	(1916 × 1148 × 1215 mm)(*3)		
Weight (approx.)		13 kg	23 kg	51 kg	55 kg		
(with basket)		(25.2 kg)(*3) (54.9 kg)(*3) (59.5 kg)(*3)					
Compatible OS (*4)		Windows 10/8.1					
	Mac OS X 10.6 ~ 10.11 / macOS 10.12 ~ 10.15 (Graphtec Studio: 10.6 - 10.15, Cutting Master 4: 10.7 - 10.15)						
Supported software ((*5)		Graphtec Studio(Mac), Cutting Maste				
Safety		PSE, UL/cUL, CE mark					
EMC		VCCI Class A, FCC Class A, CE mark					
		, , , , , , , , , , , , , , , , , , , ,					

Option		
Item	Part No.	Description
Basket for CE7000 series	PG0103	For CE7000-60
	PG0104	For CE7000-130
	PG0105	For CE7000-160
Carrier sheet table	OPH-A45	For CE7000-40 or CE7000-60
Additional push roller kit	OPH-A49	Only for CE7000-130/CE7000-160
Optional Stand	ST0118	For CE7000-60
Graphtec Pro Studio Plus	OPS682-PLS	Design software including all advanced functions (1 license)
Graphtec Pro Studio Plus for Rhinestone	OPS682-RSF	Limited edition of rhinestone function only (1 license)
Graphtec Pro Studio Plus for Auto Nesting	OPS682-ANF	Limited edition of auto nesting function only (1 license)

Supplies			
em Part No. Desc		Description	Package
Cutting blade holder	PHP33-CB09N-HS	For CB09U series blade	1 set/pack
	PHP33-CB15N-HS	For CB15U series blade	1 set/pack
Cutting blade	CB09-P	0.9mm dia. 45° angle, Supersteel	5 blades/pack
	CB09UB-5	0.9mm dia. 45° angle, Supersteel	5 blades/pack
	CB09UB-K60-5	0.9mm dia. 60° angle, for Car-film	5 blades/pack
	CB15U-5	1.5mm dia. 45° angle, for paper/cardboard	5 blades/pack
	CB15U-K30-5	1.5mm dia. 30° angle, for paper/cardboard	5 blades/pack
oupe PM-CT-001 Checking blad		Checking blade length, for PHP33 and PHP35 series	1 set/pack
Fiber-tip pen holder PHP31-FIBER		Pen holder for KF700 series pen	1 set/pack
Water-based KF700-BK		Pen (black)	10 pens/pack
fiber-tip pen	KF700-RD	Pen (red)	10 pens/pack
Ballpoint pen holder	PHP34-BALL	Pen holder for KB700 pen	1 set/pack
Oil-based ballpoint pen	KB700-BK	Pen (black)	10 pens/pack
Carrier Sheet	CR09300-A3	A3 size(*7)	2 sheets/pack
Cutting mat	PM-CR-009	For CE7000-40 replacement cutting mat	2 sets/pack
	PM-CR-010	For CE7000-60 replacement cutting mat	2 sets/pack
	PM-CR-011	For CE7000-130 replacement cutting mat	2 sets/pack
	PM-CR-012	For CE7000-160 replacement cutting mat	2 sets/pack

Item	Qty	Description
Power cord	1	The type of cord is different by destination.
USB Cable	1	2.9m long
Cutting blade holder	1	PHP33-CB09N-HS
Cutting Blade	1	CB09UB-1P
Loupe	1	PM-CT-001
Fiber-tip pen holder	1	PHP31-FIBER
Water-based Fiber-tip pen	1	KF700-BK (black)
Roll Media Tray	1	Standard accessory for CE7000-40/-60
		(* Only for CE7000-40 in Japan and US)
Stand for CE7000	1	Standard accessory for 130 / 160
DVD-ROM		User manual, Windows driver,
	1	Graphtec Pro Studio (Windows, 1 license),
		Graphtec Studio (Mac), Cutting Master4
Printed document	1	Setup Manual, Cutter Blade Manual
	' '	and Safety Manual

- CE7000-160 is not available in US & Korea.

 Operated with Graphtec specified cutting condition and media.

 For long-length cutting, the basket is used.

 HP-GL™ is a registered trademark of Hewlett-Packard Company.

 When equipped with the stand.

 Graphtec does not support software/driver used with operating systems that have become obsolete and are no longer supported by the OS developer.

 The software can be used by downloading from Graphtec website.

 It requires an Internet connection in order for activation or registration when starting the software for the first time.

 Please consider to use together with optional carrier sheet table
- *7 Please consider to use together with optional carrier sheet table "OPH-A45" for CE7000-40/60.



MDS Inovativne Tehnologije d.d.

Leskoškova cesta 9e, 1000 Ljubljana





@ info@mds~it.si



GRAPHTEC

Cutting Plotter CE7000 series

CE7000-40 / CE7000-60 / CE7000-130 / CE7000-160 (Not available in US & Korea)



Enhanced basic specification and excellent cost-effectiveness

- Supporting a cutting force of 4.41N (450gf) expands application possibilities.
- Ease of use with great media tracking on long runs.
- ARMS8.0 helps improve the productivity of print and cut.
- Improved workflow with offline output using USB memory and data management function using Barcode.
- Useful standard or optional software helps improve the efficiency of cutting operation.

* The basket in photo above is optional item

www.graphteccorp.com

Graphtec cutting plotters never stop evolving.

The cutting plotter CE7000 series has great efficiency as high as high-end model with high cost-effectiveness.

Support improve work efficiency and productivity with enhanced specifications and standard software specialized for cutting operation.
















4 sizes are available depending on the application.


Minimum mountable media width is 50mm (1.96 inch). Maximum mountable media width depends on each machine; 484mm(19 inch), 712mm(28 inch), 1372mm(54 inch)

	Media
CE7000-160	←1626mm →
CE7000-130	←1372mm ——
CE7000-60	← 712mm —→
CE7000-40	← 484mm →

and 1626mm(64 inch). Supports various cutting patterns such as perforation cut









Cutting performance that guaranties accurate 5m length cutting. (*3)

The media stocker helps stabilize the feeding of media. By adjusting the pressure of the middle push roller to the media (* 1) in three levels, it prevent media floating.

In addition, by using an optional special basket, stability in long cuts can be achieved.







Optional basket (CE7000-60/130/160)


Data output via USB flash memory without PC

The cutting data designed with Cutting Master 4 or Graphtec Pro Studio / Plus can be output directly to the cutting plotter by saving to USB flash memory and plugging in. This simplified work-flow enables users to operate without a computer.

nory format only supports FAT32. Please note that NTFS and exFAT are not supported.



Adobe Illustrator / CorelDRAW plug-in software Cutting Master 4 5th



and CorelDRAW Graphic Suite. It sends cutting data to the plotter and includes a variety of functions such as: preview, registration mark creation, tool conditions, cut job settings and more. Cutting Master 4 is easy to use and enables you to get the best performance from your plotter. Trim marks for Adobe Illustrator is finally available.

Supported OS (*4)	Windows 10/8.1, Mac OS X 10.7~macOS 10.15		
Supported software (*4)	Adobe Illustrator: CS4 (*5)~CS6,CC~2020 CorelDRAW: Graphics Suite X4~X8,2017~2019		
<main features=""></main>			

- Output by layer or color Insert weeding line
 Split an object into small pieces with tilling fund

Graphtec Pro Studio Standard Accessory **Graphtec Studio**

Software



Easy-to-use application software for creating original designs. It has many enhanced functions such as auto-shapes, shading, and editing functions. It can also configure the cutting conditions and other

Supported	Graphtec Pro Studio	Windows10/8.1
software (*4)	Graphtec Studio	Mac OS X 10.6~macOS 10.15

- Create designs using auto-shape, various line types, etc.
 Texts edit (rotate, mirror, fit-to-shape, etc.)
- Auto-trace (supporting bmp, tiff, jpeg, gif, etc. image format)
 Connectable and switchable to multiple plotters
 EPS, DXF format files and other raster format files are supported.
- Laver (*6) Output by color Insert weeding line (*6)

Graphtec Pro Studio Plus Option



Studio. It is optional software with functions for improving productivity and advanced design. Additional functions include transformation of characters and graphics, automatic sequence number insertion, bar-code creation, templates for rh creation, nesting, directional change of cutting lines, changing cutting order, and more.

Supported OS (*4) Windows 10/8.1 <Main Features of Graphtec Pro Studio Plus>

- Text and shape deformation, shadow / stripe effects Spelling check
- ect and snape deformation, snadow / stripe effects → sper lector Filter for bitmap image Power Nest (Nesting) lerialized numbering, Barcode, QR code, etc. Cutting sim
- Changing cutting order) Output by layer or color Insert weeding line
- <Main Features of Graphtec Pro Studio Plus for Rhinestone
- < Main Features of Graphtec Pro Studio Plus for Auto Nesting

* In case that using carrier sheet "CR09300-A3", Please use together with carrier sheet table "OPH-A45".

[Carrier Sheet Table]

* Available with CE7000-40 / -60.

a carrier sheet.

The Advanced Registration Mark Sensing system delivers precise Print & Cut results by using sensors to detect registration marks and perform axis alignment. Countless efficiency boosting features improve productivity for Print & Cut applications such as stickers and decals. For more information on "ARMS", please visit our website.

Data Link Function (Barcode Data Management/Continuous Cutting)

By reading the Graphtec original Barcode, CE7000 automatically detects its linked data from PC or USB flash memory. This function is available regardless of which printer or RIP software is used.

*The USB memory format only supports FAT32. Please note that NTFS and exFAT are not supported.



Continuous Cut (Data Link function)

Barcode data management allows cutting different data sequentially by detecting the "Start Mark" of the new Barcode. Sequential Print & Cut process with roll-media is now available.



Supports colored marks / specialty media

A wide variety of media types including holographic paper and reflective sheets are now compatible due to improvements of the ARMS sensor algorithm.

Sensor may not be able to read certain

Supports Adobe Illustrator "Crop Marks"

Using the plug-in software Cutting Master 4, Adobe Illustrator crop marks will be available.



Expanded Cutting Area

The expanded cutting area to include objects outside of the area enclosed by registration marks. Production efficiency is enhanced by reducing media waste.

