

BUILT FOR EXCELLENCE

Create a wealth of Large
Format applications
with ease



- Based on over 10 years of proven technology, the ColorWave 3000 series inspires confidence with its convenient, hassle-free operation, excellent print quality and outstanding reliability, when each detail counts.
- The ColorWave 3000 series is a flexible printing system that is ideal for both technical document and graphic arts print providers.
- The ColorWave 3000 series are full of smart, time-saving innovations that reduce misprints and costs.
- With automated roll switching, excellent workflow software and a full range of excellently tuned peripherals, the ColorWave 3000 series is capable of producing a broad application range with minimal operator intervention.
- Sophisticated security features safeguard your data, not only today, but also in the future.
- The ColorWave 3000 series comes in two models: the ColorWave 3600 for worry free walk up printing, and the ColorWave 3800 for users that require higher media capacity and even more media versatility.

ColorWave 3800

The ColorWave 3000 series offers hassle-free operation and high print quality in a convenient, cost-effective solution. The ColorWave 3000 series printers are built for excellence: equipped with smart, time-saving innovations and easy-to-use functionalities that reduce misprints.



PRODUCT RANGE



ColorWave 3600



ColorWave 3800



SMARTshield



CrystalPoint



POWERSync




Image Logic



ClearConnect



MediaSense



PAINT

Canon

TECHNICAL SPECIFICATIONS

STANDARD SYSTEM CONFIGURATION

4 Roll printing system

Productive Large Format Colour printer with ClearConnect multi-touch user panel

Applications

Colour and B&W Technical drawings, Maps, unfolded and folded, POP/POS posters, Graphic Arts applications like posters, wallpapers, banners, wrapping paper, fine art

Stacking systems

Integrated Top Delivery Tray, 90 sheets capacity

Multi-touch user interface

ClearConnect multi-touch user interface: Consistent look and feel from every angle of your workflow, standard including Smart Inbox, SmartAccess, printer status and Live Preview

Roll media switching

Fully automated roll media switch, to guide the media to the top delivery tray or back output depending on the user application

Workflow software

ClearConnect:
Drivers: Driver Select for Microsoft Windows, Driver Express for Adobe PostScript 3
Publishers: Publisher Select 3 for Microsoft Windows, Publisher Express for web browsers, Publisher Mobile for IOS and Android.

Starter kit (separate order)

4x 500g toner cartridges (Cyan, Magenta, Yellow, Black). 1 roll of 90 grams paper is included in the printer

Earthquake provision¹

Secure the printer against moving or tilting during an earthquake. This provision enables the user to secure the printer to a sturdy element of the building

OPTIONAL SYSTEM CONFIGURATIONS

Roll media capacity upgrade

Additional 3rd drawer to increase media capacity from 4 to 6 media rolls (800 to 1200 m1, 850 to 1280 m2)

Removable hard disk

For secure environments, hard disk can be removed from the printer system to secure data integrity

Office space saving scanning system

Scanner Express with Image Logic technology, integrated CIS scanner positioned on top of the printer to save office space

Standalone System scanner

Scanner Professional, productive Stand alone 48 bit color scanner with 1200x1200 dpi CCD technology

Stacking System

Stacker Select, up to 400 sheets capacity. Increase your delivery capacity up to 500 sheets

Folding Systems

Folder Professional, productive fullfold folder with 150 folded packages delivery capacity.
Folder Express, compact fullfold folder with 80 folded packages delivery capacity

TECHNOLOGY

Imaging technology

CrystalPoint Technology. The printer contains 8 Imaging Devices, 2 for each colour (CMYK).
Clean toner refill system, no toner dust, no residue.
No ozone emission

Automated functions

- PAINT technology (Piezo Acoustic Integrated Nozzle Technology) applies sophisticated diagnostics, maintenance and error corrections to overcome common nozzle issues that occur with conventional inkjet printers even while printing
- MediaSense technology automatically adjusts the optimum print gap between the media and the Imaging Device for every type of media. This allows you to print on thicker media (up to 800 µm/ 30 mil)
- Automated print language recognition
- Automated print mode selection (Print Assistant)
- Automated media saving function
- Automatically suggests the right print mode for your job

Toner

ColorWave 3900 TonerPearls; Cyan, Magenta, Yellow and Black, 500g/cartridge

PRODUCTIVITY

Speed (print and copy)

4 A1/D-sizes² per minute
2 A0/E-sizes³ per minute

B&W CAD: 225 A1/D-sizes per hour (113 m2/hour), 129 A0/m2/E-sizes per hour (high speed mode)
Colour CAD: 212 A1/D-sizes per hour (106 m2/hour), 120 A0/m2/E-sizes per hour (high speed mode)

First print out time⁴

<40 seconds

First copy out time⁵

<40 seconds

Print modes

9 print modes, the Print Assistant automatically determines the best print mode based on the content, without need for user intervention. Manual selection is possible.

QUALITY

Print Resolution

600 x 600 dpi

Resolution Droplet aligning accuracy

1200 dpi (corresponds to 20 microns)

Minimum line width (ISO/IEC 13660:2001E)

0.08 mm; 0.00315 in

1:1 Line accuracy

< 0.3%

SIZE AND WEIGHT

Size main engine (WxDxH)

Compact design: 2100 x 875 x 1605 mm

Shipping dimensions (WxDxH)

2271 x 1196 x 1547 mm

Weight main engine

290 kg (standard configuration)

Shipping weight main engine

376 kg (standard configuration)

ColorWave 3800

MEDIA HANDLING

Media capacity

4 or 6 rolls

Media cutting

Automatic

Maximum media capacity

4 roll: 800 m1, 850 m2; 6 roll: 1200 m1, 1280 m2;

Media sizes

Supports all sizes from 297 mm - 1067 mm, 11 in - 42 in, including standard sizes DIN, ANSI, ARCH

Media weight

60 - 200 g/m2; 16 - 53 lb; film: 2.5 - 8.0 mil

Media thickness

800 µm; 30 mill; film: 65 - 200 µm / 2,5-8 mil

Roll length

Up to 200m

Roll width

297 mm - 1067 mm, 11 in - 42 in

Roll diameter

Up to 180 mm; 71 in

Roll core diameter

3 in and 2 in cores (media on 2 in core to the external output not to the Top Delivery Tray)
Media loose on core

Roll weight

Up to 20 kg

Minimum printed length

210 mm; 8,5 in

Maximum printed length

200 m; 656 ft

Roll media type

Uncoated papers, uncoated tyvek, self-adhesive papers, self-adhesive coated vinyls, blue back papers, textile types, polypropylene films, polyester films, light block films, canvas, soft banner, instant dry photo paper, coated & uncoated non-woven wall paper (fleece), backlit film, wall paper, several natural and synthetic textiles

Custom media

Custom media support, including automatic calibration, no tooling and training required

Automatic roll media handling

- Automatic width detection
- Automatic roll media selection for optimised productivity and media saving, based on drawing size, media type, roll width and finishing
- Automatic rotation and alignment for folding
- Automatic legend detection
- Automatic roll switching when end of roll is reached
- MediaSense Technology: automatic media thickness measurement and printing height adjustment

USER INTERFACE

Description

ClearConnect multi-touch user panel

Size (WxHxD)

300 x 220 x 40 mm; 11.8 x 8.7 x 1.6 in. Touch screen: 10.4 in

Resolution

800 x 600 pixels (SVGA)

Number of colours

16.2 Million

Technology

Projective capacitive touch

Operation

3 hard buttons: [Wake-up], [Stop, interrupt, abort], [Home]
Multi-touch functions: tab, double tap, pinch, 2 finger pinch, swipe, flick and spread

Interface design

Distinctive user interface with intuitive navigation and clearly defined levels of operation

Features

View optimisation: Tilt (-4 to +45 degrees) and turn (-45 to +180 degrees) Status light (red, orange, green) USB 2.0 interface with indication light. Switch instantly between 2 languages, select from 20 languages; Czech, Danish, German, English-UK, English-US, Spanish, Finnish, French, Hungarian, Italian, Japanese, Korean, Dutch, Norwegian, Polish, Portuguese, Russian, Swedish, Chinese simplified, Chinese-traditional

CONTROLLER

Description

High performance POWERsync controller with Windows 10 IoT LTSC, 64 bits

Processor

6 Core, 6 Thread, Core i5-8500 @4.10Ghz

Memory

8 GB DDR4

Video

Intel HD Graphics, 1GHz

Hard Disk

2x 500 GB, 7200 rpm (standard)

TPM

TPM 2.0

Client operating system support

- Driver Select; Windows 8, Windows 8 64 bits, Windows 8.1, Windows 8.1 64 bits, Windows 10, Windows 10 64 bits, Windows Server 2012 64 bits, Windows Server 2012 R2 64 bits, Windows Server 2016 64 bits, Windows Server 2019 64 bits; Citrix XenApp 7.15, Citrix Virtual Apps 7 1811.1, Microfocus Enterprise Server OES 2018
- Driver Express; Windows 8, Windows 8 64 bits, Windows 8.1, Windows 8.1 64 bits, Windows 10, Windows 10 64 bits, Windows Server 2012 64 bits, Windows Server 2012 R2 64 bits, Windows Server 2016 64 bits, Windows Server 2019 64 bits; MacOS 10.13/10.14/10.15
- Publisher Select; Driver Select; Windows 8, Windows 8 64 bits, Windows 8.1, Windows 8.1 64 bits, Windows 10, Windows 10 64 bits
- Publisher Mobile; Android & IOS

Interface

2x Ethernet 100 Mbits/s, 1 Gbit/s
TCP/IP: DHCP, IPv4, IPv6, HTTPS
Discovery: APiPA, WS-Discovery, SNMP
WAVE interface

Page description language

TIFF, JPEG, HPGL, HPGL2, C4, Calcomp 906/907/951, CALS, NIRS, NIFF

Page description language(optional)

ColorWave 3800 PDF/APPE license provides access to Adobe PostScript 3 and PDF1.7. It enables the Adobe CPSI (Configurable PostScript Interpreter) and the APPE (Adobe PDF Print Engine) 4 components

Printing Protocol

LPR, FTP, WebDav, WSD print

Back Channel protocol

SNMP v3, Wave interface, WS-Discovery.

Transformations	Scaling; Scaling (scale-to-fit page, reduce when image too large to avoid clipping or to custom factor, scale page size to standard blanc too much); Shift (automatic or user defined); Adding/removing trailing/leading edge; Mirror, Area to erase (area of interest)	CLEARCONNECT WORKFLOW SOFTWARE	
Cloud support	Unlimited user and or Administrator authenticated cloud support via WebDav and/or third party provider: e.g. Microsoft SharePoint, Dropbox, Box.com, box.net, Google Drive, Microsoft OneDrive, Amazon Cloud Drive, Cloudsafe, MyDisk, The cloud user authentication can either be preconfigured by the administrator or done by the user at the time of accessing the specific cloud ⁶	Job submission	ClearConnect print workflow software enables you to print in one GO, and efficiently create and submit print jobs safely from a variety of devices and sources. The ClearConnect software suite consists of a variety of applications that all have the same user interface. Create, retrieve and/or send jobs from: • The Drivers (Driver Select for Microsoft Windows, Driver Express for Adobe PostScript 3 for Microsoft Windows or Apple OS); Easy to use printer drivers that allow you to effectively and efficiently print from any application • Publisher Select - Easily create, manage and submit complex sets of documents from your desktop – to one, or two printers at a time • Publisher Mobile - Submit print jobs via your mobile phone app supporting IOS and Android • Publisher Express - Easily submit your print jobs via the web independent of your web browser • ClearConnect User Panel - Print, Copy, Scan is as easy as using a tablet with the multi-touch user panel. Pull up a document from your Smart Inbox, USB device or external locations. Zoom and pan to different areas - even preview live while scanning or copying to avoid errors. The ColorWave 3000 series include RIP Support (eg Onyx Thrive). ⁷
Colour management	• RGB input profile (sRGB, AdobeRGB) • CMYK input profile (Euroscale coated, Euroscale uncoated, US Web coated (SWOP), US Web uncoated, ISOcoated_v2_eci_300.icc, ISOcoated_v2_eci.icc (FOGRA39), PSO Uncoated ISO12647-ECI (FOGRA47), GRACoL2006_Coated1v2.icc, SWOP2006_Coated3v2.icc, SWOP2006_Coated5v2.icc, UncoatedFogra29.icm • Grey profile (standard included in the PDF/APPE option • Rendering intent (perceptual, saturation, absolute colorimetric, relative colorimetric)		
SECURITY			
Embedded security	SMARTshield: E-shredding, IPsec, IP filtering/Access Control Lists, HTTPS, SNMP v3, audit logging, AES256 Disk Encryption, 802.1x Authentication, network protocol enable/disable, LDAP integration, Active Directory Integration, User authentication on local ClearConnect user panel and via WebTools Express (LDAP/Active Directory credentials, smart card) for scan/copy/print. Configure HTTPS Certificates, Allow disabling TLS1.0 and 1.1 protocols (no response to network scan) and enable TLS 1.2 with stronger cipher. Embedded FIPS 140-2 Certified Trusted Platform Module (TPM) and BitLocker 256 AES hard disk encryption, hard disk wipe, Configurable CA certificate, Disable Network Ports and Protocols, Security Event Logging, Single Sign-on. Options: Removable hard disk, McAfee antivirus, McAfee Application control (whitelisting)	Smart inbox	Personalised Smart Inbox with history, Manage queue, Manage history, WebTools Express, Secured controller access
Authentication	Provide secure access to device by users by keying in password on the ClearConnect multi-touch operator panel or get access with a Smart Card by connecting a card reader (including contactless). Authorisation is managed by using Active Directory	Queue management	Spool memory provides a queuing system for print and copy jobs. This enables multiple users to send print and copy jobs at the same time. Customise priority settings for copy and print jobs in the queue. The Job Queue overview gives access to job names, owners and status including required media. Jobs can be paused, deleted, and placed on top of the queue
SCANNER EXPRESS (optional)		Print management & accounting	View the counter history at preferred time periods, per job or total overview in WebTools Express. View, create, edit and delete stamp templates. Optional uniFLOW support, login your personal uniFLOW Queue on the ClearConnect User Interface. Supports manual authentication, card readers, and contactless card readers
Description	Integrated Contact Image Sensor (CIS) Colour scanner with Image Logic technology	Scan to colour inkjet	Scan directly to imagePROGRAF 600/700/800/ TX-2000/3000/4000/5200/5300/5400 series via Publisher Select 3 (hotfolder)
Scan resolution	600 x 600 dpi	Mobile and Cloud	Print from and scan to the cloud application of your choice. With the help of mobile applications such as Publisher Mobile the printer can be easily accessed and used from any location
Scan speed	15.2 m/min Black & white scanning 5.0 m/min Colour scanning	Device management	WebTools Express provide administrators the tools to manage the device remotely via the web: e.g. check printer status, define default settings for print, copy and scan, define access, security, accounting, remote shutdown, software update and restart, power on/off timer, system behaviour, queue management, license management, view, create, edit and delete stamp templates etc
Scan formats	TIFF, PDF, PDF/A, JPEG, CALS, multi-page PDF, multi-page PDF/A and multi-page TIFF	PERIPHERALS (optional)	
Scan templates	Extensive number of scan templates to standardise common scan settings and destinations	SCANNER PROFESSIONAL	
Scan protocol	FTP, SMB, scan to cloud (push to WebDAV based clouds)	Description	Charge-coupled device (CCD) colour 44 in scanner with optional upgrade to 48 in
Scan destination	Local USB flash drive, FTP, SMB, Smart Inbox on Controller, Optional Local Home folder (LDAP), mobile device via Publisher Express, WebDAV Clouds	Scan resolution	1200 x 1200 dpi (9600 x 9600 dpi interpolated)
Scan naming	Preset naming with auto numbering for productive scanning or file name on the ClearConnect user panel	Scan speed	23 m/min (150 dpi) 4.6 m/min (600 dpi)
Original width	208 mm - 965 mm; 8.2 in - 38 in, automatic width detection	Scan formats	Multipage PDF (PDF/A) and TIFF, JPEG, JPEG 2000, PNM, PNG, BMP, TIFF (Raw, G3, G4, LZW, JPEG) AutoCAD DWF, JBIG, DjVu, DICOM, PCX, Postscript, EPS, Raw data
Original length	208 mm - 16000 mm; 8.2 in- 630 in, automatic length detection	Scan templates	Unlimited
Original thickness	Maximum 0.8 mm; 0.03 in (non-rigid documents)	Original width	1270 mm; 50 in
Effective scan width	932 mm	Original length	200 m
Zoom (copy)	1:1, Scale to media size, Scale to standard format, Custom: 10 - 1000%	Colour depth/ colour output	48 bit colour, 16 bit greyscale / 24 bit colour, 8 bit greyscale, bitonal, enhanced halftone
Original types presets	Blueprint, Coloured original, Dark original, Folded lines/ text, Lines/text standard, Lines/text draft, Photo, Map, Artwork	Scan width	44 model: 1118 mm; 44 in / 48 model: max. 1220 mm; 48 in
Size scanner (WxDxH)	1097 x 308 x 140 mm; 43 x 12 x 5.5 in.	Connections	1 USB Port 3.0 Interface 1 GBit Fast Ethernet with TCP/IP based Interface
Weight scanner	25 kg; 55 lbs	Embedded controller	64 bit Linux, Intel i3, quad core processor, 16 Gigabyte RAM, 320GB HDD for very long scans
ENVIRONMENTAL		Size scanner (HxWxD)	1070 x 1425 x 507 mm; 42 x 56 x 20 in
Sound power level	Standby and sleep: 4.7 B(A) Print mode: 6.9 B(A)	Weight scanner	60 kg / 132 lbs
Sound pressure level	Standby and sleep: 36 dB Print mode: 57 dB	FOLDER EXPRESS 3011	
Ozone concentration	Zero	Description	Compact integrated automated fullfold folder
Heat emission	Ready: 215 W; Active: 325 W	Folding speed	Folding speed 1 - 12 m/min ; 39 - 472 in/min
Operating temperature	15 – 35 °C (recommended: 20 – 27 °C); 59 - 95 °F (recommended: 68 - 81 °F)	Dimensions folder (WxDxH)	1780 x 860 x 1037-1253 mm; 70 x 34 x 40-50 in
Operating humidity	20 – 80% RH (recommended: 30 – 60% RH)	Delivery capacity	80 A0/E size folded packages (80 g/m2)
Power requirements	100 - 240 V; 50/60Hz	FOLDER PROFESSIONAL 6011/6013	
Power consumption	Sleep mode: <2.5 W Ready mode: 215 W Active mode: 325 W	Description	Integrated productive fullfold folder with automated, manual folding and unfold output
Safety/ EMC marks & environmental labels	CE, TÜV GS, CETECOM, c-UL-US, CB, RCM, ENERGY STAR 3.0, FEMP, EPEAT, CCC, EAC, FCC Class A, VCCI Class A, RoHS, Greenguard Gold	Folding speed	2.5 - 10 m/min ; 1.6 - 6.6 in/sec (29 m/min ; 11.8 in/sec with optional High Speed License)
Recyclables	Printer: made of steel and highly recyclable plastics, min 86% of the engine can either be upcycled or recycled. Toner: cartridge packaging reused as maintenance cassette and made of recyclable plastic. Prints: very good deinkability when recycled	Dimensions Folder (WxDxH)	1837 x 1634 x 1227 mm (6011) 2157 x 1634 x 1227 mm (6013)

Delivery capacity (standard delivery belt)	150 A0/E size folded packages (80 gr/m2)
Reinforcement (tab unit)	Folder Professional 6013 only
STACKER SELECT	
Description	Productive integrated high capacity stacker with air separation
Capacity	up to 400 sheets
Media width	216 mm (8.5 in) - 1067 mm (42 in)
Media length	200 mm (7.9 in) - 1220 mm (48 in)
Media weight	60 - 160 g/m2
FOOTNOTES:	
1	Excluding cable/chain and mounting material
2	D size (34 x 22 in) / A1 size (841 x 594 mm)
3	E size (44 x 34 in) / A0 size (1189x 841 mm)
4	1 A1 landscape print to back output, in fastest print mode, from ready mode.
5	1 copy made in A1 landscape. Print to back output, in fastest print mode, background compensation off,, from ready mode.
6	Based on current third party support
7	Adobe and Postscript are either registered trademarks or trademarks of Adobe Systems Inc. in the United States and/or other countries; Microsoft, Windows, SharePoint and OneDrive are registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries; Amazon is a registered trademark or trademark of Amazon Corporation in the United States and/or other countries; Box and the Box logo are including without limitation either trademarks, service marks or registered trademarks of Box.com(UK) Ltd.; ARC is a trademark of Synopsis Inc. I the United States and/or other countries; CloudSafe is a trademark of CloudSafe GmbH &Co. KG; Dropbox is a trademark of Dropbox, Inc.; MyDisk is a trademark of MyDisk Ltd.; iOS is a registered trademark or trademark of Apple inc. in the United States and/or other countries



MDS Inovativne Tehnologije d.d.
Leskoškova cesta 9e, 1000 Ljubljana



386 1 586 79 33



www.mds-it.si



info@mds-it.si

